



ASTRON CERCHIO

INSTALLATION TYPE:
WALL-MOUNTED

GU10

IP65



	MADE IN ITALY			GU10 ø50mm max 15W 1301C 1305A-B 1303	GU10 110-120V~ 50/60Hz GU10 ø35mm max 10W 1301A-B - 1302A
025.652 REV03	IP65	LED 110-277V	LED 1301D 17W 110-277V 1301E 10W 110-277V		

1

2

3

4

5

6

7

8

9

10

11

12

GU10

a1

a2

a3

a4

a5

LED

b1

b2

b3

b4

P.2

sales@gordonbullard.com

www.byiba.com

1 877-964-4646

ETL

LISTED

US

991 South Gull Lake Dr.

Richland, MI 49083

USA

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

© Bullard & Comany 2025 All Rights Reserved



IMPORTANT

To ensure equipment safety you must carefully follow the instructions below. This leaflet must be kept handy by personnel entrusted with all ordinary and extraordinary maintenance.

- Before any installation or maintenance operation on the bulb, make sure it is disconnected from power
- Fit the correct bulbs, according to the type and power indicated on the lamp data label.
- Make sure the lamp technical features are compatible with the use you are going to make of it.
- Should you have any doubt, refer to the dealer or ask an electrician.
- When connecting to the mains, follow the correct colour code for power cables: (N) blue, (L) brown or black and, only for class I equipment, (T) yellow/green.
- When lamps are to be fitted to the wall directly through their ceramic parts, fasten the fixing screws lightly, to avoid breaking the ceramic.
- To clean the lamp on the outside, use a soft cloth, possibly wet. Do not use solvents or abrasive products. No liquid must get in contact with the lamp interior parts.
- Do not touch the equipment with dirty hands.



= Class I equipment, must be connected to an earth terminal.



= Double insulated lamp, does not need earthing.



= Electrical equipment in class III, electrical safety guaranteed by low voltage tension, does not require grounding



= Minimum distance to be observed from all lit up objects.



= Replace immediately the safety glass, if damaged, with the original part.



= The lamp uses low pressure bulbs, and needs no protection glass.



= The equipment at the end of its life must be collected separately from other waste.