BYİBA
LIGHT

BOULDER
(FLEXIBLE CONDUCTIVE TEXTILE BELT TRACK) (MODULAR CEILING SYSTEMS)





Boulder is a decorative LED pendant featuring an opal glass globe and a distinctive textile belt suspension. Its softly glowing diffuser provides gentle, evenly distributed illumination while adding a rounded accent to the interior. Designed for a compatible flexible conductive textile belt system, it can be arranged individually or grouped at different heights. Boulder creates an inviting atmosphere above dining tables, in lounges, and throughout contemporary hospitality spaces.

12W / 945lm / CRI >90

2700K / 3000K / 3500K / 4000K

Ø: 7.87″ (20.0 cm)
Ø: 11.81″ (30.0 cm)

BYIBA
LIGHT

CODE:
BY-BLDR-VL



PROJECT

SPEC TYPE

NOTES

MATERIAL
Aluminum/Opal / frosted spherical glass diffuser.

ELECTRICAL SYSTEM
24V DC;
24V/48V;
confirm the selected belt, feed and driver voltage before ordering.

LIGHTING
Integrated LED OSRAM

LIGHT DISTRIBUTION
Diffuse

CRI
CRI >90

INSTALLATION
Belt-mounted module; tool-free snap-fit / magnetic attachment. Repositionable along a compatible flexible belt.

Surface / Pendant system configurations. Belt route and suspension follow approved layout.

ELECTRICAL / CONTROLS
Low-voltage belt system; confirm ordered supply and driver/controller.

WARRANTY
3 years

LED | 24V DC | 48V DC | IP20 | STANDARD

ETL LISTED c US

WE WELCOME ALL CUSTOM ORDERS

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

©2026 All Rights Reserved

WWW.BYIBA.COM

OUTDOOR | TECHNICAL | DECORATIVE


Contact Us:
sales@gordonbullard.com
www.byiba.com
1 877-964-4646

Updated 10/25/2026

BYIBA LIGHT

CODE:

BY-BLDR-VL



PROJECT

SPEC TYPE

NOTES

HOW TO ORDER:

Example:

CODE: BY-BLDR-VL-D1-K30-BL-DIM

1 DIMENSIONS:

Height	H: 7.83″ (19.9 cm)
Width	W: 2.64″ (6.7 cm)
Connector dimension	1.20″ (3.05 cm)

2 DIAMETER:

-D1	Ø: 7.87″ (20.0 cm)
-D2	Ø: 11.81″ (30.0 cm)

3 LIGHT SOURCE:

LED OSRAM / 12W / 945lm / CRI >90

4 CCT:

-K27	2700K	-K40	4000K
-K30	3000K	-TW	Tunable white
-K35	3500K		

5 FINISH OPTIONS:

-BL	Black	-BG	Beige
-TR	Terra Red	-OW	Off-White
-GR	Green	-CUS	Custom on request

6 DIMMING OPTIONS:

-TR	Triac,	-TUYA	Tuya
-DIM	0/1–10V	-ZB	Zigbee
-DALI	DALI		

Wired options and wireless ecosystems depend on the selected compatible driver/controller.

LED | 24V DC | 48V DC | IP20 | STANDARD

WE WELCOME ALL CUSTOM ORDERS

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

©2026 All Rights Reserved

WWW.BYIBA.COM

OUTDOOR | TECHNICAL | DECORATIVE

Contact Us:
sales@gordonbullard.com
www.byiba.com
1 877-964-4646

Updated 10/25/2026